



7/16 Din Male to 4.3-10 Male Right Angle Quick Disconnect RG401 (Flex Form 0.27") | 123-14FFDMHMRQ-XX-P | 123e.com

Part Number: 123-14FFDMHMRQ-XX-P

7/16 Din Male to 4.3-10 Male Right Angle Quick Disconnect 1/4 inch FlexForm™ Low PIM factory made jumper

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	7/16 Din Male
Connector B	4.3-10 Male Right Angle Quick Disconnect
Outer Diameter	7.00±0.15 mm
Inner Conductor	Silver-coated Copper
Outer Conductor	Tin Soaked Copper Braid
Jacket Color	White
Insulation	Solid PTFE

ELECTRICAL SPECIFICATIONS

Frequency Range	up to 18Ghz
Impedance	50 Ohm
PIM	-175dBc
Return Loss	≤-27dB @3GHz, ≤-24dB @6GHz

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-55°C to +125°C
RoHS Compliance	Yes
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.