



**3/8" Super Flex 4.3-10 Male to 4.3-10 Male Low PIM Jumper |123-38SFHMHM |123e.com**  
Part Number: 123-38SFHMHM-XX-P

4.3-10 Male to 4.3-10 Male welded onto 3/8" Super Flex cable, Low PIM factory made jumper. 123eWireless factory made assemblies are optimized to produce low passive third order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance and averages -165dBc. MADE in the USA.

#### CROSS REFERENCE

Alternative To F2A-HMHM, SLJ38SP-64M64M, FSJ2-50, SCF38-50J, LSF2-50

#### PHYSICAL SPECIFICATIONS

|                        |  |
|------------------------|--|
| Connector A            | 4.3-10 Male                                  |
| Connector B            | 4.3-10 Male                                  |
| Inner Conductor        | Copper-Clad Aluminum 1.90mm (0.075in)        |
| Outer Conductor        | Helically Corrugated Copper 6.40mm (0.252in) |
| Jacket Color           | Black  |
| Insulation             | Physically Foamed PE 4.70mm (0.185in)        |
| Jacket Material        | PE - UV Resistant                            |
| Maximum Bending Radius | 2.00"  |

#### ELECTRICAL SPECIFICATIONS

|                 |                    |
|-----------------|--------------------|
| Frequency Range | Max 10.2 GHz       |
| Impedance       | 50±2 Ohm           |
| Peak Power      | 13.2 kW            |
| PIM             | -165 dBc IEC 62037 |
| Return Loss     | -30 db             |

#### ENVIRONMENTAL SPECIFICATIONS

|                       |                  |
|-----------------------|------------------|
| Operating Temperature | -55°C to +85°C   |
| Weather Standard      | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.