



7/16 Din Female to 7/16 Din Male RG401 (Flex Form 0.27") | 123-14FFDFDM | 123e.com
Part Number: 123-14FFDFDM-XX-P

DIN (7/16) Female to DIN (7/16) Male 1/4 inch FlexForm™ Low PIM factory made jumper

CROSS REFERENCE

Alternative To CXTM02M-10-I

PHYSICAL SPECIFICATIONS

| | |
|-----------------|-------------------------|
| Connector A | 7/16 Din Female |
| Connector B | 7/16 Din Male |
| Outer Diameter | 7.00±0.15 mm |
| Inner Conductor | Silver-coated Copper |
| Outer Conductor | Tin Soaked Copper Braid |
| Jacket Color | White |
| Insulation | Solid PTFE |

ELECTRICAL SPECIFICATIONS

| | |
|-----------------|----------------------------|
| Frequency Range | up to 18Ghz |
| Impedance | 50 Ohm |
| PIM | -162dBc |
| Return Loss | ≤-27dB @3GHz, ≤-24dB @6GHz |

ENVIRONMENTAL SPECIFICATIONS

| | |
|-----------------------|------------------|
| Operating Temperature | -55°C to +125°C |
| RoHS Compliance | Yes |
| Weather Standard | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.