



**1/2" Flexible (LDF4-50A) 7/16 Din Male to 7/16 Din Male With EasyBoots Low PIM jumper**  
| **123-1DMDM-XX-P-EB** | **123e.com**  
Part Number: 123-1DMDM-XX-P-EB

7/16 Din Male to 7/16 Din Male With EasyBoot welded onto 1/2 inch Flexible Rated Coaxial Cable, black PE jacket. This jumper cable is MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

#### CROSS REFERENCE

Alternative To LDMWDMW-12, LDMWDMW-12-30

#### PHYSICAL SPECIFICATIONS

Connector A	7/16 Din Male with EasyBoot
Connector B	7/16 Din Male with EasyBoot
Outer Diameter	0.307in (7.8mm)
Inner Conductor	Copper clad aluminum wire
Outer Conductor	Helical corrugated copper
Jacket Color	Black
Insulation	PE Spline
Jacket Material	PE - UV Resistant
Maximum Bending Radius	1.18"

#### ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50±2 Ohm
PIM	-156dBc
Return Loss	≤-30dB @3GHz, ≤-24dB @6GHz

#### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +80°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.