



1/2" Flexible Coaxial Cable Plenum |123-1P-50| 123e.com

Part Number: 123-1P-50

1/2" flexible annular cable is ideal for Low PIM applications where cable flexibility is necessary. This indoor plenum-rated cable is ideally suited for DAS applications including raised flooring systems and air handling ducts. The off-white cable color allows for easy camouflage in an indoor setting.

CROSS REFERENCE

Alternative To HL4RPV-50, AL4RPV-50, ICA12-50JPL, AP6012J50

PHYSICAL SPECIFICATIONS

| | |
|--------------------|-----------------------------|
| Flexibility | Standard |
| Outer Diameter | 1/2in |
| Inner Conductor | Copper-Clad Aluminum |
| Outer Conductor | Annularly Corrugated Copper |
| Jacket Color | White |
| Bend Radius Single | 4.8in, (120mm) |

ELECTRICAL SPECIFICATIONS

| | |
|-----------------|--------|
| Frequency Range | 3 GHz |
| Impedance | 50 Ohm |

ENVIRONMENTAL SPECIFICATIONS

| | |
|-----------------------|------------------------|
| Operating Temperature | -20C to +80C |
| Weather Standard | IEC 60068 40/ 085 / 21 |

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.