

**RG402 (141) PTFE Cable, Blue Jacket, Plenum | 123-14FMP-50 | 123e.com**  
Part Number: 123-14FMP-50



The 123-14FMP-50 is a high-performance, semi-flexible RG402 coaxial cable designed to withstand extreme temperatures ranging from **-55°C to +125°C**. Engineered for durability and reliable signal transmission, this cable features a **silver-plated copper inner conductor** and a **solid PTFE insulation** for optimal electrical properties. The **tin-soaked copper braid outer conductor** and **FEP jacket** provide superior shielding and protection.

**Key Features:**

- **Impedance:**  $50 \pm 2 \Omega$
- **Max Operating Voltage:** 1.9 kVRMS
- **Signal Delay:** 4.7 ns/m
- **Propagation Velocity:** 70.8%
- **Screening Effectiveness:** 100 dB
- **Max Operating Frequency:** 34 GHz
- **VSWR (DC~3000 MHz):**  $\leq 1.15$
- **Bending Radius (Single):** 8 mm
- **Bending Radius (Repeat):** 40 mm
- **Attenuation:** Low nominal attenuation across a wide frequency range (e.g., 0.37 dB/m at 800 MHz, 1.29 dB/m at 7300 MHz)

**CROSS REFERENCE**

Alternative To RG402 Plenum

**PHYSICAL SPECIFICATIONS**

Outer Diameter	.141"
Outer Conductor	Tin-soaked copper Braid
Jacket Color	Blue
Insulation	Solid PTFE
Jacket Material	FEP Blue

**ELECTRICAL SPECIFICATIONS**

Frequency Range	up to 34GHz
Impedance	50 Ohm
Inner Construction	Silver-plated Copper

**ENVIRONMENTAL SPECIFICATIONS**

Operating Temperature	-55°C to +125°C
-----------------------	-----------------

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.