



## 4.3-10 Female 1/4" Superflexible Field Installed |123-14SFHF |123e.com

Part Number: 123-14SFHF

4.3-10 Female Field Termination Connector for 1/4" Superflexible Cable, 123-14SF-50 or equivalent. This connector is easily installed onto any manufacturer's 1/4" Superflexible cable including Commscope FSJ1-50A, and RFS SCF14-50J. This field termination design uses two wrenches and a stripping tool to install onto the cable

### CROSS REFERENCE

Alternative To	AXP-4F-14S
----------------	------------

### PHYSICAL SPECIFICATIONS

Mating Cycles	100
Connector A	4.3/10
Gender	Female
Inner Conductor	SPRING COPPER
Insulation	TPX

### ELECTRICAL SPECIFICATIONS

Frequency Range	DC 3GHz
Impedance	50 ohms
Insertion Loss	0.05 dB
PIM	≤-160(2*43dBm)
VSWR	1.15

### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to 85°C
RoHS Compliance	Yes
Weather Standard	IEC 60068 40 / 085/ 21

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.