



N Male solder center body connector for 1/4in Super Flexible Cable | 123-14SFNMS | 123e.com

Part Number: 123-14SFNMS

The 123-14SFNMS is a N male solder-center, solder-body connector designed for use with 1/4" SuperFlex and FlexForm (RG401) coaxial cables. It delivers reliable signal integrity from 0-6 GHz with 50-ohm impedance and Low PIM performance of <-160 dBc, making it ideal for wireless infrastructure, DAS, and telecom applications.

Constructed with a silver-plated brass inner conductor, ternary alloy-plated brass body, silicone rubber gasket, and PTFE insulation, this connector is built for durability across an operating temperature range of -40°C to +155°C. Compatible with CommScope FSJ1-50A and equivalent 1/4" SF cables.

PHYSICAL SPECIFICATIONS

Options	Solder Type
Connector A	N Male
Gender	Male
Inner Conductor	Brass, Silver Plating
Body	Brass, Ternary Alloy Plating
Insulation	PTFE

ELECTRICAL SPECIFICATIONS

Frequency Range	0-6GHz
Impedance	50 Omhs
PIM	< -160 dBc
VSWR	≤1.15(0-3GHz) ≤1.3 (3-6GHz)

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to 155°C
RoHS Compliance	Yes

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.