



Jumper, Single Pair, SM I/O, LC(D)-LC(D) | 123-F1D2-1A4DD-XX-HS | 123e.com
Part Number: 123-F1D2-1A4DD-XX-HS

This LC/Uniboot to LC/Uniboot FTTA fiber assembly has heat shrink joining the cable and connector, offering a ruggedized solution. It is singlemode Indoor/Outdoor 2 Fiber Assembly. Bend insensitive with a black jacket.

CROSS REFERENCE

Alternative To 942-97308-10XXX, 942-97308-10035

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Uniboot with ruggedized heat shrink
Connector B	LC/UPC Uniboot with ruggedized heat shrink
Fiber Count	2
Breakout Length Side A	N/A
Breakout Length Side B	N/A
Furcation	
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	> 50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.