



**LC/UPC to LC/UPC 2 Fiber Duplex Singlemode Indoor Plenum with Pulling sock | 123-F1X2-4A477-XX-PS | 123e.com**

Part Number: 123-F1X2-4A477-XX-PS

LC/UPC to LC/UPC 4.4MM Bend 2 Fiber Duplex Singlemode Indoor Plenum with 2mm breakouts and a pulling sock for easy installation. Patch cords are custom made with Corning's SMF-28 Ultra optical fiber and meet or exceed GR-326 standards. Each assembly is optically tested, bagged, and serialized for traceability and quality purposes.

### CROSS REFERENCE

Alternative To

### PHYSICAL SPECIFICATIONS

Options	with pulling sock
Connector A	LC/UPC
Connector B	LC/UPC
Fiber Count	2
Breakout Length Side A	6 Inches
Breakout Length Side B	6 Inches
Furcation	2mm
Outer Diameter	4.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Yellow
Jacket Material	Indoor Plenum

### ATTENUATION

Attenuation @ 1550nm	0.4 dB/km
Attenuation @ 1310nm	0.5 dB/km

### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
-----------------------	----------------

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.