



**LC/UPC to LC/UPC Simplex Singlemode, Bend Insensitive Fiber, Zipcord | 123-F1M2-1A366 | 123e.com**

Part Number: 123-F1M2-1A366

LC/UPC to LC UPC Simplex Singlemode, Bend Insensitive Fiber, Zipcord Jumper. Each assembly is optically tested, bagged, and serialized for traceability and quality purposes.

#### CROSS REFERENCE

Alternative To FB-L98B-A1150-3000

#### PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Simplex
Connector B	LC/UPC Simplex
Fiber Count	2
Outer Diameter	1.6mm
Fiber Type	SMF-28® Ultra
Jacket Color	Yellow
Jacket Material	Indoor Riser

#### ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

#### OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

#### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
-----------------------	----------------

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.