



Ruggedized Armored LC/UPC-LC/UPC 2F, Single Mode I/O Riser| 123-F4X2-1A4DD-XX-OM | 123e.com

Part Number: 123-F4X2-1A4DD-XX-OM

Armored LC/UPC uniboot to LC/UPC uniboot duplex, Singlemode 2 fiber round distribution indoor/outdoor jumper with ruggedized overmolds on both connectors to added extra strength and durability. Designed for Ericsson base station functionality for typical interconnection between RRU and BBU. CPRI, LTE, and 5G ready.

CROSS REFERENCE

Alternative To FJ-2SM-015A

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Uniboot with overmold
Connector B	LC/UPC Uniboot with overmold
Fiber Count	2
Breakout Length Side A	N/A
Breakout Length Side B	N/A
Outer Diameter	5.0 mm ±0.2
Fiber Type	G652D MM62.5/125 G657
Jacket Color	Black
Jacket Material	LSZH, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	Stainless steel armored tube

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.