



**SC/APC-SC/APC 2F Duplex, Single Mode I/O Jumper | 123-F1D2-1A244 | 123e.com**  
Part Number: 123-F1D2-1A244

SC/APC-SC/APC duplex, Singlemode 2 fiber round distribution indoor/outdoor jumper. Designed for Ericsson base station functionality for typical interconnection between RRU and BBU. CPRI, LTE and 5G ready.

### CROSS REFERENCE

Alternative To

### PHYSICAL SPECIFICATIONS

Connector A	SC/APC
Connector B	SC/APC
Fiber Count	2
Breakout Length Side A	6"
Breakout Length Side B	6"
Furcation	2 mm
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

### ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

### OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.