



SC/APC-LC/UPC 2F Duplex, Single Mode I/O Riser with a Pulling Sock | 123-F1D2-1A447-XX-PS-001 | 123e.com

Part Number: 123-F1D2-1A447-XX-PS-001

SC APC to LC UPC duplex, Singlemode 2 fiber round distribution indoor/outdoor jumper with a pulling sock for easy installation. Designed for Ericsson base station functionality for typical interconnection between RRU and BBU. CPRI, LTE and 5G ready.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	SC/APC
Connector B	LC/UPC Duplex w/Pulling Sock
Fiber Count	2
Breakout Length Side A	8 Inch
Breakout Length Side B	6 Inch
Furcation	2 mm
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.