



**PUSHLOK(TM) OPTAP CONVERTER / LC UPC CONNECTOR, DUPLEX, CLEARCURVE(R) LBL,  
2F SST-DROP(R), DIELECTRIC | 123-D30402JB4FDXXXF-P | 123e.com**

Part Number: 123-D30402JB4FDXXXF-P

**Evolv® SST-Drop™ with Pushlok® Technology 2F Pushlok to LC Duplex, Dielectric**

This versatile cable is engineered for aerial, direct burial, and conduit installations, making it ideal for for outside plant (OSP) FTTx access networks. Compatible with Corning's Evolv® Optical Tap Terminals, it offers fully sealed environmental protection and quick, hassle-free connections. Designed to save space and speed up installations. This assembly directly compares to Corning D30402JB4FD035F-P.

\*All trademarks mentioned are the property of their respective owners.

#### CROSS REFERENCE

Alternative To D30402JB4FD035F-P, D30402JB4FD050F-P, D30402JB4FD075F-P

#### PHYSICAL SPECIFICATIONS

|                        |                        |
|------------------------|------------------------|
| Connector A            | LC/UPC Duplex          |
| Connector B            | Evolv Pushlok (SC/APC) |
| Fiber Count            | 2                      |
| Breakout Length Side A | 6IN                    |
| Breakout Length Side B | 53IN ± 1IN             |
| Outer Diameter         |                        |
| Fiber Type             | SMF-28E                |
| Jacket Color           | Black                  |
| Jacket Material        | SST Drop               |

#### ATTENUATION

|                      |            |
|----------------------|------------|
| Attenuation @ 1550nm | 0.25 dB/km |
| Attenuation @ 1310nm | 0.40 dB/km |

#### OPTICAL SPECIFICATIONS

|                |                                  |
|----------------|----------------------------------|
| Insertion Loss | Bi Dir. 1310nm, 1550nm, < 0.5 dB |
| Return Loss    | >50 dB                           |

#### ENVIRONMENTAL SPECIFICATIONS

|                       |                |
|-----------------------|----------------|
| Operating Temperature | -20°C to +70°C |
| Varmint Rating        | None           |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.