



LC/UPC to LC/UPC 12F, Single Mode I/O Riser with 12IN fanout and pulling sock | 123-F3X12-1A477-XX-PS-003 | 123e.com

Part Number: 123-F3X12-1A477-XX-PS-003

LC/UPC to LC/UPC Single Mode 12 fiber (6 pair) round distribution indoor/outdoor jumper with 12 inch fanout and a pulling sock for easy installation.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Duplex
Connector B	LC/UPC Duplex
Fiber Count	12
Breakout Length Side A	12 inch fanout
Breakout Length Side B	12 inch fanout
Furcation	2 mm
Outer Diameter	5.8mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.