



LC/UPC-LC/UPC Armored Simplex SM 1F with Pulling sock| 123-F4X1-1A466-XX-PS-002 | 123e.com

Part Number: 123-F4X1-1A466-XX-PS-002

Discrete, 1 single mode fiber, 5 mm armored cable, flexible 6in breakout on each end, LC to LC, variant length.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC
Connector B	LC/UPC
Fiber Count	1
Breakout Length Side A	6IN
Breakout Length Side B	6IN
Furcation	2 mm
Outer Diameter	5.0 mm $\pm$ 0.2
Fiber Type	G652D MM62.5/125 G657
Jacket Color	Black
Jacket Material	LSZH, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	1.0mm stainless steel armored tube

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.