



Armored ODC/RFX Male - LC/UPC Clipped 16F, Single Mode | 123-F4X16-1A4F7-XXF-PS | 123e.com

Part Number: 123-F4X16-1A4F7-XXF-PS

ARMORED 16 Fiber LC/UPC to ODC/RFX Male SM 16 fiber round distribution indoor/outdoor jumper Designed for Ericsson base station functionality for typical interconnection between RRU and BBU. CPRI, LTE, and 5G ready.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	ODC/RFX Male
Connector B	LC/UPC Duplex
Fiber Count	16
Breakout Length Side A	20IN
Breakout Length Side B	8IN
Furcation	2 mm
Outer Diameter	5.0 mm $\pm$ 0.2
Fiber Type	G652D MM62.5/125 G657
Jacket Color	Black
Jacket Material	

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	Stainless steel armored tube

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.