

**Armored LC/UPC-LC/UPC 2F, Single Mode I/O Riser| 123-F4X2-1A4DD-XX-HS | 123e.com**
Part Number: 123-F4X2-1A4DD-XX-HS

Armored LC/UPC uniboot to LC/UPC uniboot duplex, Singlemode 2 fiber round distribution indoor/outdoor jumper with heat shrink on both connectors to added extra strength and durability. Designed for Ericsson base station functionality for typical interconnection between RRU and BBU. CPRI, LTE, and 5G ready.

CROSS REFERENCE

Alternative To

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	Stainless steel armored tube

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Uniboot with heatshrink
Connector B	LC/UPC Uniboot with heatshrink
Fiber Count	2
Breakout Length Side A	N/A
Breakout Length Side B	N/A
Fiber Type	G652D MM62.5/125 G657
Jacket Color	Black
Jacket Material	LSZH, I/O
Outer Diameter	5.0 mm ±0.2

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.