

LC-UPC-LC-UPC 2F Duplex, Single Mode I/O Jumper | 123-F1D2-1A277-XX-001 | 123e.com
Part Number: 123-F1D2-1A277-XX-001



LC-UPC-LC-UPC duplex, Singlemode 2 fiber round distribution indoor/outdoor jumper. Designed for Ericsson base station functionality for typical interconnection between RRU and BBU. CPRI, LTE, and 5G ready.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC
Connector B	LC/UPC
Fiber Count	2
Breakout Length Side A	3"
Breakout Length Side B	24"
Furcation	2 mm
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.
Please contact us at sales@123ewireless.com for any queries.