

SC/UPC-LC/UPC 2F Duplex, Single Mode I/O Riser | 123-F1D2-1A427-XX-003 | 123e.com
Part Number: 123-F1D2-1A427-XX-003



SC/UPC to LC UPC duplex, Singlemode 2 fiber round 5.2MM distribution indoor/outdoor jumper with 24 inch breakouts on each end. Designed for Ericsson base station functionality for typical interconnection between RRU and BBU. CPRI, LTE and 5G ready.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	SC/UPC Duplex
Connector B	LC/UPC Duplex
Fiber Count	2
Breakout Length Side A	24IN
Breakout Length Side B	24IN
Furcation	2 mm
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.