



## SC/UPC-LC/UPC 2F Duplex, Single Mode I/O Riser with a Pulling Sock | 123-F1D2-1A427-XX-PS | 123e.com

Part Number: 123-F1D2-1A427-XX-PS

SC/UPC to LC UPC duplex, Singlemode 2 fiber round distribution indoor/outdoor jumper with a pulling sock for easy installation. 6 inch breakouts on each end. Designed for Ericsson base station functionality for typical interconnection between RRU and BBU. CPRI, LTE, and 5G ready.

### CROSS REFERENCE

Alternative To

### PHYSICAL SPECIFICATIONS

|                        |                              |
|------------------------|------------------------------|
| Connector A            | SC/UPC Duplex                |
| Connector B            | LC/UPC Duplex w/Pulling Sock |
| Fiber Count            | 2                            |
| Breakout Length Side A | 6IN                          |
| Breakout Length Side B | 6IN                          |
| Furcation              | 2 mm                         |
| Outer Diameter         | 5.4mm                        |
| Fiber Type             | SMF-28® Ultra                |
| Jacket Color           | Black                        |
| Jacket Material        | OFNR, I/O                    |

### ATTENUATION

|                      |            |
|----------------------|------------|
| Attenuation @ 1550nm | 0.25 dB/km |
| Attenuation @ 1310nm | 0.40 dB/km |

### OPTICAL SPECIFICATIONS

|                |          |
|----------------|----------|
| Insertion Loss | < 0.5 dB |
| Return Loss    | >50 dB   |

### ENVIRONMENTAL SPECIFICATIONS

|                       |                |
|-----------------------|----------------|
| Operating Temperature | -20°C to +70°C |
| Varmint Rating        | None           |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.