

**Armored LC/APC-LC/APC 2F, Single Mode I/O LSZH | 123-F4X2-1A499-XX-PS | 123e.com**  
Part Number: 123-F4X2-1A499-XX-PS



Armored LC/APC-LC/APC Indoor/Outdoor 5.0mm Armored LSZH SM 2 Fiber Round Distribution.

**CROSS REFERENCE**

Alternative To

**PHYSICAL SPECIFICATIONS**

Connector A	LC/APC Duplex
Connector B	LC/APC Duplex
Fiber Count	2
Breakout Length Side A	6IN
Breakout Length Side B	6IN
Furcation	2 mm
Outer Diameter	5.0 mm ±0.2
Fiber Type	G652D MM62.5/125 G657
Jacket Color	Black
Jacket Material	LSZH, I/O

**ATTENUATION**

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

**OPTICAL SPECIFICATIONS**

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

**ENVIRONMENTAL SPECIFICATIONS**

Operating Temperature	-20°C to +70°C
Varmint Rating	1.0mm stainless steel armored tube

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.