



**SC/APC-Optitap (SC/APC) 1F Simplex, Single Mode I/O Riser | 123-F1S1-1A4H4 | 123e.com**  
Part Number: 123-F1S1-1A4H4

1 Fiber, Singlemode, SC/APC to Optitap (SC/APC), I/O Riser. Compatible with Corning's Optisheath® multiport terminals. Designed for Ericsson 2203, 2205, and RRUS radios, available in ArmorFlex. OptiTap® is a registered trademark of Corning.

## CROSS REFERENCE

Alternative To

## PHYSICAL SPECIFICATIONS

Connector A	SC/APC
Connector B	Optitap (SC/APC)
Fiber Count	1
Breakout Length Side A	6IN
Breakout Length Side B	12IN
Furcation	2 mm
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

## ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

## ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.