123eWireless
30412 Esperanza, Rancho Santa Margarita
CA 92688, (888) 263-6000
sales@123ewireless.com



LC/UPC to LC/UPC 2 Fiber Simplex Singlemode Indoor Plenum | 123-F1X2-4A466 | 123e.com
Part Number: 123-F1X2-4A466

LC/UPC to LC/UPC 4.4MM Bend 2 Fiber Simplex Singlemode Indoor Plenum with 2MM breakouts. Patch cords are custom made with Corning's SMF-28 Ultra optical fiber and meet or exceed GR-326 standards. Each assembly is optically tested, bagged, and serialized for traceability and quality purposes.

CROSS REFERENCE	
Alternative To	020202R9120003M, SURG02LCLCRXXUX-3M
PHYSICAL SPECIFICATIONS	
Connector A	LC/UPC
Connector B	LC/UPC
Fiber Count	2
Breakout Length Side A	3 Inches
Breakout Length Side B	3 Inches
Outer Diameter	4.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Yellow
Jacket Material	Indoor Plenum
ATTENUATION	
Attenuation @ 1550nm	0.4 dB/km
Attenuation @ 1310nm	0.5 dB/km
ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature	-20°C to +70°C

Thank you visiting 123eWireless.
Please contact us at sales@123ewireless.com for any queries.