

**LC/UPC-Optitap (SC/APC) 2F Armored I/O Duplex, Single Mode | 123-F4X2-1A4H7-XX-PS | 123e.com**

Part Number: 123-F4X2-1A4H7-XX-PS

2 Fiber, Singlemode, LC/UPC- Duplex Optitap (SC/APC), I/O Armored LSZH. Compatible with Corning's Optisheath® multiport terminals. Designed for Ericsson 2203, 2205, and RRUS radios, available in ArmorFlex. OptiTap® is a registered trademark of Corning.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Duplex
Connector B	Optitap (SC/APC) Duplex
Fiber Count	2
Breakout Length Side A	36IN
Breakout Length Side B	36IN
Furcation	2 mm
Outer Diameter	5.0mm ±0.2
Fiber Type	G652D MM62.5/125 G657
Jacket Color	Black
Jacket Material	LSZH, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-25°C to +80°C
Varmint Rating	Armored tube □ Stainless Steel

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.