

**LC/UPC Uniboot with FiberSeal to Optitap SC/APC, SST Drop Cable, Singlemode, 2 Fiber | 123-F6X2-5A4DH-XX-FS | 123e.com**

Part Number: 123-F6X2-5A4DH-XX-FS

LC/UPC Uniboot with FiberSeal - OptiTap (SC/APC), I/O Drop Cable, Singlemode, 2 Fiber. This cable is fitted for Aerial, direct burial, and conduit applications. Corning SST-Drop dielectric cables offer the ease of installation of standard ALTOS cables in an easy-access, single-tube design. The dielectric version eliminates any bonding and grounding requirements. The cables are RDUP (RUS) listed and offer exceptional crush resistance. Compatible with Corning's Optisheath multiport terminals. Designed for Ericsson 2203, 2205, and RRUS radios. OptiTap® is a registered trademark of Corning. This assembly is comparable to Commscope FHBDW-H2M22.

**CROSS REFERENCE**

Alternative To	FHBDW-H2M22
----------------	-------------

**PHYSICAL SPECIFICATIONS**

Connector A	LC/UPC Uniboot with FiberSeal
Connector B	Optitap (SC/APC)
Fiber Count	2
Breakout Length Side A	24IN
Breakout Length Side B	24IN
Outer Diameter	
Fiber Type	SMF-28E
Jacket Color	Black
Jacket Material	SST Drop

**ATTENUATION**

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

**OPTICAL SPECIFICATIONS**

Insertion Loss	Bi Dir. 1310nm, 1550nm, < 0.5 dB
Return Loss	>50 dB

**ENVIRONMENTAL SPECIFICATIONS**

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.