



**N Female to N Male Low Loss 240 | 123-14NFNM | 123e.com**  
Part Number: 123-14NFNM

N Female to N Male low loss 240 assembly, comparable to Times Microwave LMR®-240 50 Ohms coax cable. This RF jumper is UL listed indoor/outdoor riser-rated GPS unit Jumper.

#### CROSS REFERENCE

Alternative To

#### PHYSICAL SPECIFICATIONS

|                 |                   |
|-----------------|-------------------|
| Connector A     | N Female          |
| Connector B     | N Male            |
| Coax Cable Type | Low Loss 240      |
| Outer Diameter  | 0.24 (in)         |
| Jacket Color    | Black             |
| Jacket Material | PE - UV Resistant |

#### ELECTRICAL SPECIFICATIONS

|                 |              |
|-----------------|--------------|
| Frequency Range | 698-2200 MHz |
| Impedance       | 50 Ohm       |
| Return Loss     | -18db        |

#### ENVIRONMENTAL SPECIFICATIONS

|                       |                |
|-----------------------|----------------|
| Operating Temperature | -40°C To +85°C |
| Weather Standard      | IP 67          |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.