



QMA Female to QMA Male Attenuator, 10dB 2 Watt | 123-QMA10dB2W | 123e.com
Part Number: 123-QMA10dB2W

2W, 10dB RF Attenuator (DC-6GHz, QMA-Male to QMA-Female)

This high-performance RF attenuator is designed for superior signal management across a wide frequency band of DC to 6 GHz. Its key features include:

- **Wide Frequency Range:** Supports DC to 6 GHz for versatile applications.
- **Multi-Technology Compatibility:** Ideal for 2G, 3G, 4G, and LTE networks.
- **Low VSWR:** Ensures minimal signal reflection for optimal performance.
- **Broad Application Use:** Perfect for in-building solutions and other RF systems.

Durable and reliable, this attenuator is equipped with a QMA-male to QMA-female interface for seamless integration. It's an essential component for fine-tuning signal levels in telecommunications and network installations.

ELECTRICAL SPECIFICATIONS

| | |
|-----------------|---------|
| Attenuation | 10dB |
| Average Power | 2W@25°C |
| Frequency Range | DC-6GHz |
| Impedance | 50 ohm |
| VSWR | ≤1.25 |

ENVIRONMENTAL SPECIFICATIONS

| | |
|-----------------------|-----------|
| Operating Temperature | -30C~+65C |
|-----------------------|-----------|

PHYSICAL SPECIFICATIONS

| | |
|-------------|------------|
| Connector A | QMA Male |
| Connector B | QMA Female |

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.