



30412 Esperanza, Rancho Santa Margarita
CA 92688, (888) 263-6000
sales@123ewireless.com

RF 240, 1.0/2.3 Male to SMA Right Angle Male | 123-141023MSMAR-XX | 123e.com

Part Number: 123-141023MSMAR

1.0/2.3 Male to SMA Male low loss 240 LMR240 style cable UL Riser rated indoor/outdoor assembly.

1.0/2.3 Maic to SMA Maic 10W 1033 240 El	mile 40 Style cubic of Misch rated madolyoutagon assembly.
CROSS REFERENCE	
Alternative To	LMR240, CNT-240
PHYSICAL SPECIFICATIONS	
Coax Cable Type	Low Loss 240 (LMR240 equivalent)
Connector A	1.0/2.3 Male
Connector B	SMA Right Angle Male
Outer Diameter	0.24 (in)
Jacket Color	Black
Jacket Material	PE - UV Resistant
ELECTRICAL SPECIFICATIONS	
Attenuation	7.0 dB/100ft @ 900 MHz =(Nom)
Impedance	50 Ohm
Insertion Loss	≤-1.29 dB
Return Loss	≤-24 dB
Frequency Range	698-2200 MHz
ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature	-40°C To +85°C
Weather Standard	IP 67