

**3/8" Super Flex 7/16 Din Male to 4.3/10 Male Low PIM Jumper |123-38SFDMMH  
|123e.com**

Part Number: 123-38SFDMMH-XX-P

7/16 Din Male to 4.3/10 Male welded onto 3/8" Super Flex cable, Low PIM factory-made jumper. 123eWireless factory-made assemblies are optimized to produce low passive third-order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. MADE in the USA.

**CROSS REFERENCE**

Alternative To F2A-HMDM-3M-P

**ELECTRICAL SPECIFICATIONS**

Frequency Range Max 10.2 GHz

Impedance 50±2 Ohm

Peak Power 13.2 kW

PIM -165 dBc IEC 62037

Return Loss -30 db

**ENVIRONMENTAL SPECIFICATIONS**

Operating Temperature -55°C to +85°C

Weather Standard IEC 68 40/85/ 21

**PHYSICAL SPECIFICATIONS**

Inner Conductor Copper-Clad Aluminum 1.90mm (0.075in)

Insulation Physically Foamed PE 4.70mm (0.185in)

Maximum Bending Radius 2.00"

Outer Conductor Helically Corrugated Copper 6.40mm (0.252in)

Connector A 7/16 Din Male

Connector B 4.3/10 Male

Jacket Color Black

Jacket Material PE - UV Resistant

Thank you visiting 123eWireless.  
Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.