



4.3-10 Male 40 Watt RF Load Terminator, Low PIM | 123-HMT40-P | 123e.com
Part Number: 123-HMT40-P

40W Low PIM Termination Load (600-6000MHz, -160dBc, 4.3/10-male) also known as a dummy load.

- Wide Frequency Band 600-6000MHz
- 2G/3G/4G/LTE Coverage
- Low VSWR
- Low Passive Intermodulation -160dBc
- Widely used for Indoor Solutions

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Weight	0.55 (kg)
Connector A	4.3/10 Male
Gender	Male

ELECTRICAL SPECIFICATIONS

Average Power	40 Watts
Frequency Range	600-6000MHz
Impedance	50 ohm
PIM	$\leq -160\text{dBc}@2*43\text{dBm}$
VSWR	$600\text{--}3800\text{MHz} \leq 1.30$ $3800\text{--}6000\text{MHz} \leq 1.35$

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	$-30^{\circ}\text{C} \sim +65^{\circ}\text{C}$
-----------------------	--

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.