



4.3-10 Male 200 Watt RF Load Terminator | 123-HMT200-6G | 123e.com

Part Number: 123-HMT200-6G

200W RF Load (DC-6GHz, 4.3-10 Male)

High-Power Termination for Wireless Infrastructure and In-Building Systems

The **123-HMT200-6G** is a rugged, high-performance RF load designed for applications across a wide frequency range from DC to 6 GHz. Engineered for reliability, this 200-watt load supports 2G, 3G, 4G, and LTE bands, making it ideal for use in DAS (Distributed Antenna Systems), base stations, and RF testing environments.

Key Features:

- **Wide Frequency Range:** DC to 6 GHz for broad compatibility
- **High Power Handling:** Supports up to 200W average power
- **Low VSWR:** Ensures minimal signal reflection (≤ 1.3)
- **Durable Design:** Operates in harsh conditions from -30°C to $+65^{\circ}\text{C}$
- **Industry-Standard Connector:** 4.3-10 Male interface
- **Compact & Solid Build:** Weighs 1.5 kg with a sleek black finish

Applications:

- In-building wireless systems
- Wireless network infrastructure
- Test and measurement setups

Upgrade your RF system with a load that delivers performance, durability, and reliability—exactly where you need it most.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Weight	3.95 lbs
Connector A	4.3-10 Male
Gender	Male

ELECTRICAL SPECIFICATIONS

Average Power	200 Watts
Frequency Range	DC-6Ghz
Impedance	50 ohm
VSWR	≤ 1.3

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-86F to 329F (-30C to 165C)
Weather Standard	IEC 60068 40 / 085/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.