



SC/APC - OptiTap SC/APC SMF-28E, 1F ROC 900 DROP, TONEABLE, W/PULLING SOCK | 123-F6X1-5A4H5 | 123e.com
Part Number: 123-F6X1-5A4H5

SC/APC - OptiTap SC/APC , I/O Drop Cable, Singlemode, 1 Fiber.

This Corning SST-Drop™ cable combine the easy installation of standard ALTOS® cables with a single-tube, easy access design. These cables are RDUP (RUS) Listed and deliver exceptional crush resistance, making them ideal for rugged environments and underground installations. The toneable version features a separable toning conductor and copper element for effortless buried cable detection and clear identification during installation.

Compatible with Corning's Optisheath multiport terminals. Designed for Ericsson 2203, 2205, and RRUS radios.

OptiTap® and ALTOS® are registered trademarks of Corning.

CROSS REFERENCE

Alternative To 001EB1-14101A20, FHD-HJ1B

PHYSICAL SPECIFICATIONS

Connector A	SC/APC
Connector B	Optitap (SC/APC)
Fiber Count	1
Breakout Length Side A	12in
Breakout Length Side B	6in
Outer Diameter	2.0mm
Fiber Type	SMF-28E
Jacket Color	Black
Jacket Material	SST Drop, Direct Buried, Duct, Toneable

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	Bi Dir. 1310nm, 1550nm, < 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
-----------------------	----------------

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.