



**5G LC/HD PPT - LC/UPC 1F Simplex, Single Mode I/O Riser | 123-F1S1-1A4Q6-XX-002 | 123e.com**

Part Number: 123-F1S1-1A4Q6-XX-002

1 Fiber, Singlemode, LC/HD PPT to LC/UPC, I/O Riser. The LC/HD PPT side is made to fit into the JONHON connector and Samsung Radio, available in ArmorFlex. OptiTap® is a registered trademark of Corning.

## CROSS REFERENCE

|                |                   |
|----------------|-------------------|
| Alternative To | FR-N-1SSM-01-30FS |
|----------------|-------------------|

## PHYSICAL SPECIFICATIONS

|                        |               |
|------------------------|---------------|
| Connector A            | LC/HD PPT     |
| Connector B            | LC/UPC        |
| Fiber Count            | 1             |
| Breakout Length Side A | N/A           |
| Breakout Length Side B | 9IN           |
| Furcation              | 2 mm          |
| Outer Diameter         | 5.4mm         |
| Fiber Type             | SMF-28® Ultra |
| Jacket Color           | Black         |
| Jacket Material        | OFNR, I/O     |

## ATTENUATION

|                      |            |
|----------------------|------------|
| Attenuation @ 1550nm | 0.25 dB/km |
| Attenuation @ 1310nm | 0.40 dB/km |

## ENVIRONMENTAL SPECIFICATIONS

|                       |                |
|-----------------------|----------------|
| Operating Temperature | -20°C to +70°C |
|-----------------------|----------------|

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.