



**LC/UPC simplex to Optitap SC/APC, SST Drop Cable, Singlemode, 1 Fiber | 123-F6S1-5A4H6 | 123e.com**

Part Number: 123-F6S1-5A4H6

LC/UPC - OptiTap (SC/APC), I/O Drop Cable, Singlemode, 1 Fiber. This cable is fitted for Aerial, direct burial, and conduit applications. Corning SST-Drop dielectric cables offer the ease of installation of standard ALTOS cables in an easy-access, single-tube design. The dielectric version eliminates any bonding and grounding requirements. The cables are RDUP (RUS) listed and offer exceptional crush resistance. Compatible with Corning's Optisheath multiport terminals. Designed for Ericsson 2203, 2205, and RRUS radios. OptiTap® is a registered trademark of Corning.

#### CROSS REFERENCE

Alternative To

#### PHYSICAL SPECIFICATIONS

Connector A	LC/UPC
Connector B	Optitap (SC/APC)
Fiber Count	1
Breakout Length Side A	
Breakout Length Side B	
Outer Diameter	
Fiber Type	SMF-28E
Jacket Color	Black
Jacket Material	SST Drop

#### ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

#### OPTICAL SPECIFICATIONS

Insertion Loss	Bi Dir. 1310nm, 1550nm, < 0.5 dB
Return Loss	>50 dB

#### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.