

**ST/UPC-LC/UPC 2F Duplex, Single Mode I/O Riser | 123-F1D2-1A417-XX | 123e.com**  
Part Number: 123-F1D2-1A417-XX



ST/UPC to LC UPC duplex, Singlemode 2 fiber round distribution indoor/outdoor jumper. 12 inch breakouts on each end.

**CROSS REFERENCE**

Alternative To

**PHYSICAL SPECIFICATIONS**

Connector A	ST/UPC Duplex
Connector B	LC/UPC Duplex
Fiber Count	2
Breakout Length Side A	12IN
Breakout Length Side B	12IN
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

**ATTENUATION**

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

**OPTICAL SPECIFICATIONS**

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

**ENVIRONMENTAL SPECIFICATIONS**

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.